

Version	2.1	Date	1/26/25
Prepared By	JC		

PRODUCT SPECIFICATION				
Category	Backlit Panel			
Item Number	9755			
Stock Code	FPNL50SW/2X4/8CCT3			
Mounting	Recessed			
Housing Color	White			
ELECTRICAL CHARACTERISTICS				
Rated Wattage (W)	30/40/50	Replacement Wattage (W)	120-130	
Tested Wattage (W)	30/40/50			
Input Voltage (V)	120-277V			
Voltage Frequency (Hz)	50/60	Surge Protect Level	2.5KV	
Input Current (A)	0.12	Dimmable	0-10V	
Power Factor	>0.9	AUX (12V) Line	Yes	
THD	-			
PHOTOMETRIC CHARACTERISTICS				
Lumen (lm)	3,300 4,400 5,500	CCT (K)	3CCT (35/40/50K)	
Efficacy (lm/w)	110	Beam Angle (°)	115°	
CRI	>80			
GENERAL CHARACTERISTICS				
Operating Temperature (°F)	-4°F ~ 104°			
Storage Temperature (°F)	-40°F ~ 185°			
IP Rating	Damp Location			
IK Rating	-			
Rated Life (Hrs)	50,000			
Warranty (Yrs)	5			
ACCESSORIES				
Item #	Stock Code	Description		
7346	BAEM8-PNL-50BC/MV-A	8W Emergency Driver for 100-277V for Back-Lit Flat Panels		
PRODUCT DIMENSIONS				
Width- in / (mm)	47.8"	1213		
Height- in / (mm)	1.40"	35		
Depth- in / (mm)	23.70"	603		
IK Rating	-			
Weight (lbs)	-			
Mounting Height (ft)	-			
Cable Length (ft)	-			
CERTIFICATIONS				
UL/ETL	ETL/cETL	CEC		
NSF/ETL Sanitation		JA8		
Energy Star		FCC	✓	
DLC	5.1 Standard	RoHS	✓	
DOCUMENTS				
LM79	✓	IES File	✓	
LM80	✓	Dimmer List		
COMMENTS				
<p>naturalLED © For informational purposes only. Specifications Subject to Change Without Notice</p>				