## **All-Terior LED Wall Sconce**

## START FROM HERE

- Make sure **POWER** is **COMPLETELY OFF** at the fuse box
- Have your fixture installed by a qualified licensed electrician
- Prepare everything in a clear area
- · Wear gloves at all time during this installation
- Read instructions carefully before you start assembly
- Keep this installation sheet for future reference

**Technical Support:** 1-855-855-8926

## Please Note:

- This Kuzco LED fixture comes with pre-wired LED module(s)
- Unless instructed, Do Not touch any part of the LED module(s) as any unnecessary contact with the module could cause permanent damage
- Use ELV (Electronic Low Voltage) type of dimmer for dimming application
- 120V input

- 1. Remove fixture from its original package
- Separate mounting plate (1c) and anchor plate
  (2a) from canopy (2c) by removing canopy screws
  (2d) and anchor plate screws (2b)
- Attach mounting plate (1c) to electrical junction box (1a) using junction box screws provided (1d) in hardware package
- **4.** Make proper electrical connections (**black** to **hot** "L", **white** to **neutral** "N", **ground** to "**GND**") with wire nuts (**1b**) provided in hardware package
- **5.** Attach anchor plate (2a) to mounting plate (1c) with anchor plate screws (2b)
- **6.** Attach canopy (2c) to anchor plate (2a) with canopy screws (2d)
- 7. To prevent moisture from entering the electrical junction box (1a) and causing a short, seal around the top and side perimeter between the fixture and the wall surface with weather resistant caulking (See Illustration 1). The space at the bottom should be left un-caulked to prevent moisture build up





