

Specifications



Photo is representative



Eaton C25ENF440B

Eaton definite purpose contactor, Quick, 40A, 208-240 Vac, 50/60 Hz, Open with metal mounting plate, 15-50A, two- and three-pole, 40A, Contactor, Four-pole, 50A, Box lugs (posidrive setscrew) and quick connect terminals, Non-reversing

General specifications

PRODUCT NAME	Eaton definite purpose contactor
CATALOG NUMBER	C25ENF440B
UPC	782113536606
PRODUCT LENGTH/DEPTH	3.38 in
PRODUCT HEIGHT	3.75 in
PRODUCT WIDTH	2.68 in
PRODUCT WEIGHT	2.3 lb
WARRANTY	1 year
COMPLIANCES	RoHS Compliant
CERTIFICATIONS	UL Recognized CSA Certified
CATALOG NOTES	Resistive Load rating per pole
PRODUCT TYPE	Definite purpose contactor



Powering Business Worldwide

Product specifications

AMPERAGE RATING	40A
NUMBER OF POLES	Four-pole
TYPE	Non-reversing
COIL	208-240 Vac, 50/60 Hz
ENCLOSURE	Open with metal mounting plate
FRAME SIZE	15-50 A, two-pole and three-pole
INDUCTIVE FULL LOAD	40 A
MODEL	Contactator
RESISTIVE LOAD	50 A
TERMINALS	Box lugs (posidrive setscrew) and quick connect terminals (side-by-side)
CONNECTION	Quick

Resources

CATALOGS	Motor Control and Protection, Definite Purpose Contactors and Starters, Volume 5, Tab 4
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - C25ENF440B

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

