


TUBE ARCHITECTURAL DS-WS08

WAC LIGHTING

LED Wall Mounts



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

FEATURES

- High performance exterior rated LED wall mount light
- Fixture can install upside down to alter light distribution
- Solid aluminum construction
- 5 year warranty

SPECIFICATIONS

| | |
|------------------------|---|
| Input: | Universal voltage 120V - 277VAC, 50/60Hz |
| Dimming: | Electronic low voltage (ELV) : 100% - 5% 0-10V: 100% - 1% |
| Light Source: | High output 3 Step Mac Adam Ellipse COB Rated life of 60,000 hours at L70 |
| Finish: | Electrostatically powder coated, white, black, bronze and graphite |
| Standards: | IP65 rated, ETL & cETL wet location listed, Energy Star® 2.2 rated Title 24 JA8-2016 Compliant |
| Operating Temp: | -13°F to 122°F (-25°C to 50°C) |

ORDERING NUMBER

| Diameter | Watt | Beam | Angle | Color Temp | CRI | Reference Lumen | Output ¹ CBCP | Efficacy (lm/w) | Light Distribution | Finish | |
|----------|----------------------------|-----------------------------|-------|------------|-------|-----------------|--------------------------|-----------------|--------------------|--------|--|
| DS-WS08 | 8" 46W | S Straight up or down | 18° | 927S | 2700K | 90 | 3080 | 15187 | 67 | | BK Black WT White BZ Bronze GH Graphite |
| | | | | 27S | 2700K | 85 | 3865 | 19064 | 84 | | |
| | | | | 930S | 3000K | 90 | 3275 | 16156 | 71 | | |
| | | | | 30S | 3000K | 85 | 3935 | 19387 | 86 | | |
| | | | | 35S | 3500K | 85 | 4030 | 19872 | 88 | | |
| | | | | 40S | 4000K | 85 | 4095 | 20195 | 89 | | |
| | 8" 34W | N Straight up or down | 25° | 927S | 2700K | 90 | 3185 | 10536 | 68 | | |
| | | | | 27S | 2700K | 85 | 4000 | 13226 | 87 | | |
| | | | | 930S | 3000K | 90 | 3390 | 11208 | 74 | | |
| | | | | 30S | 3000K | 85 | 4070 | 13450 | 88 | | |
| | | | | 35S | 3500K | 85 | 4170 | 13786 | 91 | | |
| | | | | 40S | 4000K | 85 | 4240 | 14010 | 92 | | |
| | 8" 34W | F Straight up or down | 35° | 927S | 2700K | 90 | 3015 | 5475 | 66 | | |
| | | | | 27S | 2700K | 85 | 3785 | 7211 | 82 | | |
| | | | | 930S | 3000K | 90 | 3210 | 6111 | 70 | | |
| | | | | 30S | 3000K | 85 | 3850 | 7334 | 84 | | |
| | | | | 35S | 3500K | 85 | 3945 | 7517 | 86 | | |
| | | | | 40S | 4000K | 85 | 4010 | 7639 | 87 | | |
| 8" 34W | F Away from the wall | N/A | 927A | 2700K | 90 | 3020 | | 66 | | | |
| | | | 27A | 2700K | 85 | 3790 | | 82 | | | |
| | | | 930A | 3000K | 90 | 3210 | N/A | 70 | | | |
| | | | 30A | 3000K | 85 | 3855 | | 84 | | | |
| | | | 35A | 3500K | 85 | 3950 | | 86 | | | |
| | | | 40A | 4000K | 85 | 4015 | | 87 | | | |
| 8" 34W | F Towards the wall | N/A | 927B | 2700K | 90 | 3020 | | 66 | | | |
| | | | 27B | 2700K | 85 | 3790 | | 82 | | | |
| | | | 930B | 3000K | 90 | 3210 | N/A | 70 | | | |
| | | | 30B | 3000K | 85 | 3855 | | 84 | | | |
| | | | 35B | 3500K | 85 | 3950 | | 86 | | | |
| | | | 40B | 4000K | 85 | 4015 | | 87 | | | |

DS-WS08-_____ - _____ ¹Reference output shows 46W output. Multiply by 0.8 to determine output for 34W combinations.

Example: DS-WS08-F930A-WT

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760