



SPEKTRUM+

TRULUX LIGHTING SYSTEMS

TASK LIGHTING

DOWNLIGHTING

LINEAR LIGHTING
PRO DEC G40 E17 LAMP

ARCHITECTURAL LIGHTING

POWER SUPPLIES

Features

- SMD LED powered by on-board driver for 120V AC use in intermediate base (E17) sockets
- Nickel base resists corrosion
- Ultra clear glass lenses
- Dimmable with most CL or TRIAC dimmers*
- IP65 rated for wet location use
- cULus Listed for indoor/outdoor use
- Sold in boxes of 25 and cases of 200

Available CCT



2400K 2700K

Dimming Options

- CL (10-100%*)
- TRIAC (10-100%*)

Listing / Ratings



Pro Dec G40 E17

Traditional globe style LED G40 E17 lamps for direct replacement of 11W incandescent versions, saving 87% in running costs.

Technical Information

Series	PG40
Base	E17
Input Voltage	120V AC, 60Hz
CCT	2400K / 2700K
Wattage	1W
Lumens	Up to 55Lm (see individual product)
IP Rating	IP65
Dimmable	10-100%*
Rating	cULus Listed; Suitable for indoor/outdoor use
Rated Life	25,000 hrs

*Minimum loads will apply

Ordering Information

PG40-E17-UWW	Transparent / Ultra Warm White (2400K) / 25Lm
PG40-E17-WW	Transparent / Warm White (2700K) / 32Lm