

T8 INSTANT FIT T8 TUBES

PROJECT:

SCHEDULE:

DATE:

PREPARE BY:

NOTES:

DESCRIPTION

naturaLED® Instant-Fit T8 easiest way to upgrade your fluorescent fixture to an LED lighting system. Our Instant-Fit T8 fits into an existing fluorescent lighting system. Utilizes the existing electrical T8 fluorescent ballast without re-wiring. Our instant fit tubes come in variety of lengths from 2-ft, 3-ft, 4-ft, and 8-ft.

APPLICATIONS

Retails, restaurants, hospitalities, offices, schools

FEATURES

- DLC Standard
- Damp Location
- UL Listed
- NSF Certified
- Color Temp: 3500K, 4000K, 5000K
- Power Factor: >0.9
- Beam Spread: 325°
- Non-dimmable
- CRI: >80
- Operating temperature: - 4°F - 113°F / - 4°F - 104°F
- Instant Fit/ Plug and Play (UL Type A)
- Compatible with electronic fluorescent ballast*
- Base: Medium Bi-Pin G13
- Length: 2-ft, 3-ft, 4-ft, 8-ft
- 5 Years Warranty
- 50,000 hrs rated average life

*check compatibility list



Rated Life 50,000 Hours
Warranty 5 Years

BASE TYPE

T8



SAMPLE NUMBER LED13T8/FR18/840/IF

STYLE	WATTAGE	SERIES	WATTAGE	CRI/COLOR TEMP	TYPE
LED	13	T8	FR18	840	IF
LED Lighting	13 Watt	T8 Tubes	Frosted 1,800 lumens	CRI 80 4000K	Instant Fit



INSTANT FIT T8 TUBES

TUBE LUMINAIRES

ORDERING

*P= Premium DLC / *S = Standard DLC

Watts (W)	Ordering Code	Description	CCT (K)	Lumens (Lm)	Equivalent Wattage	Length	Base	UL Damp	DLC (S/P)
10	4558	LED10T8/24FR12/840/IFG1	4000K	1,250	17W	2-ft	Bi-Pin	•	S
10	4559	LED10T8/24FR12/850/IFG1	5000K	1,250	17W	2-ft	Bi-Pin	•	S
12	4551	LED12T8/36FR14/840/IFG1	4000K	1,450	17W	3-ft	Bi-Pin	•	S
12	4552	LED12T8/36FR14/850/IFG1	5000K	1,450	17W	3-ft	Bi-Pin	•	S
13	4582	LED13T8/FR18/840/IF	4000K	1,800	32W	4-ft	Bi-Pin	•	S
13	4583	LED13T8/FR18/850/IF	5000K	1,800	32W	4-ft	Bi-Pin	•	S
16	4584	LED16T8/FR22/840/IF	4000K	2,200	32W	4-ft	Bi-Pin	•	S
16	4585	LED16T8/FR22/850/IF	5000K	2,200	32W	4-ft	Bi-Pin	•	S
10	5988	LED10T8/24FR12/840/IFG1	4000K	1,156	17W	2-ft	Bi-Pin	•	-
10	5850	LED10T8/24FR11/835/IFG1	3500K	1,150	17W	2-ft	Bi-Pin	•	-
10	5852	LED10T8/24FR11/850/IFG1	5000K	1,150	17W	2-ft	Bi-Pin	•	-
11	5891	LED11T8/36FR14/840/IF	4000K	1,400	25W	3-ft	Bi-Pin	•	-
11	5892	LED11T8/36FR14/850/IF	5000K	1,400	25W	3-ft	Bi-Pin	•	-


INSTANT FIT T8 TUBES

TUBE LUMINAIRES


*P= Premium DLC / *S = Standard DLC

DIMENSIONS


10W (2-ft)
0.24-lbs




12W (3-ft)
0.35-lbs



13W / 16W (4-ft)
0.43-lbs




38W (8-ft)




PHOTOMETRICS CHART


10 Watt (2-ft)




12 Watt (3-ft)



13 Watt (4-ft)



16 Watt (4-ft)



PACKAGE

Case Qty 25 pcs

