

PRODUCT OVERVIEW

A standard output, wet location flexible 120V plug-in or hardwire LED linear tape for architectural coves, indoor steps, bannisters, exterior recesses and other constructs where even, energy saving LED illumination is specified. 5 year warranty. Do not submerge. **Factory cut only - cutting in field will void ETL label and warranty.**

NOTE: Each run requires power connector (see Connectors and Accessories next page).

FEATURES

- 120V operation (no power supply required)
- Wet location - IP65
- Cord and plug or hardwire power connector (replaceable fuse protected)
- Tape encased in UV inhibiting water resistant clear poly flexible sheath
- Dimmable (ELV/Triac - Lutron - Skylark - Selv-300P)
- 2700K, 3000K, 4000K, Red, Green, Blue, Amber
- 120° viewing angle
- Configured by factory in 4 inch increments
- Maximum run: 163 feet (Limit of 4 sections for maximum run Consult factory for other combinations)
- Mounting options: Clips or PVC / aluminum channel
- Frosted lens and channel covers available (see below)

SPECIFICATIONS

- ELECTRICAL**

 - 120V
 - 2.0 watts per foot

OPTICS

 - 90+ CRI

LUMENS

 - 27K (140lm/ft), 30K (150lm/ft), 40K (160lm/ft)

OPERATING TEMP

 - -4 to 122°F (-20 to +50°C)

- LABEL**

 - IP65
 - ETL

WARRANTY

 - 5 years
 - Do not install in an application that is not easily accessed for service.

ORDERING INFORMATION


	-		-		-	
Model	Output	Color Temp.	Feet - Inches			
V120	SO	2700K (27)	XXX-X			
		3000K (30)				
		4000K (40)				
		Amber (AM)				
		Blue (BL)				
		Green (GR)				
		Red (RD)				

Project Name

Type

Catalog #

Date



CUTTABLE EVERY 4"


HOW TO SPECIFY VISION120 AND CREATE A CATALOG NUMBER

Standard Output (163' Max.)
Specify by the foot / inches - **minimum cut is 4"**

Example: To order an 8'-4" length of 2700K tape,
specify: **V120-SO-27-8-4**



V120 state of the art connectors insuring a professional connection.



Product Video



SCAN ME

Product Configurator



SCAN ME

CONNECTORS AND ACCESSORIES

Catalog No.	Description
V120-PC-4	4' POWER CONNECTOR - CORD AND PLUG
V120-PC-8	8' POWER CONNECTOR - CORD AND PLUG
V120-PCHW-4	4' POWER CONNECTOR - HARDWIRE
V120-PCHW-8	8' POWER CONNECTOR - HARDWIRE
V120-TTC-6	5-3/8" TAPE TO TAPE FLEXIBLE CONNECTOR
V120-TTC-12	12-1/2" TAPE TO TAPE FLEXIBLE CONNECTOR
V120-TTC-18	15-1/2" TAPE TO TAPE FLEXIBLE CONNECTOR
V120-TTC-24	23-1/4" TAPE TO TAPE FLEXIBLE CONNECTOR
V120-3M-VHB-15	15' LONG X 1/2" WIDTH DOUBLE-SIDED MTG. TAPE
V120-CHL-4	4' ALUMINUM MOUNTING CHANNEL - LENS SOLD SEPARATELY
V120-CHL-4-LENS	FROSTED LENS FOR 4' ALUMINUM CHANNEL
V120-CHL-6	6' ALUMINUM MOUNTING CHANNEL - LENS SOLD SEPARATELY
V120-CHL-6-LENS	FROSTED LENS FOR 6' ALUMINUM CHANNEL
V120-CHL-P-4	VISION120 4' PVC MOUNTING CHANNEL (LENS NOT AVAILABLE)
V120-CHL-P-6	VISION 120 6' PVC MOUNTING CHANNEL (LENS NOT AVAILABLE)
V120-MC	VISION 120 MOUNTING CLIPS - USE 1 PER FOOT MIN. (BAG OF 10)
V120-ECC	END CAP COVERS (2) FOR ALUMINUM CHANNEL WITH LENS. WHITE
V120-90L	VISION120 90° LEFT CONNECTOR
V120-90R	VISION120 90° RIGHT CONNECTOR
SHWC-V120	LUXCONTROL VISION 120 CONTROLLER

CONNECTORS DIAGRAMS

