PANDORA WS25350

WALL



DESCRIPTION

PROJECT


Dual square profile linear aluminum arms with rectangular wall mount. Inset opal polymeric diffusers. Finely textured plate or powder-coated finish. Wall emitting lights with rotational adjustment.



SPECIFICATION DETAILS

Fixture Dimensions	W50" x H4-5/8" x E3-7/8"
Light Source	LED with DC Driver
Wattage	41W
Total Lumens	2980lm
Delivered Lumens	BK-1585lm; BN-1410lm*; WH-2187lm;
Voltage	120V
Color Temperature	3000K
CRI (Ra)	90CRI
Optional Color Temps	2700K - 5000K Available, Minimum Order Quantities Apply
LED Rated Life	50,000 hours
Dimming	100% - 10%, TRIAC or ELV Dimmer (Not Included)
Diffuser Details	White Acrylic Diffuser
ADA Compliant	Yes
Location	Dry
Compliance	T24-JA8; ADA;
Illumination Direction	Fontlight Illumination
Mounting Style	All Orientation; Wall;
CEC Title 24 JA8	Yes, JA8-22
Canopy Dimensions	W5-3/8" x H4-5/8" x E3/8"

- $\ensuremath{^{\star}}$ For custom options, consult factory for details.
- * For warranty information, please visit www.kuzcolighting.com/warranty





19054 28TH AVENUE SURREY - BC V3Z 6M3 CANADA COMMENT

