



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Watson LED Outdoor Sconce WTNW Series

Features

Simplistic design. Down light with wall wash effect. Ideal use in entrances or anywhere general outdoor lighting is needed. Provides lighting in residential, commercial and hospitality applications. Meets ADA requirements. Fixture mounts to standard junction box (not included).

Construction

Fabricated aluminum construction. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

All metal parts are powder coated in White or Black.

Diffuser

Frosted white glass bottom diffuser.

Electrical

Input 120-277 VAC 60 HZ.
0-10V dimming (120-277V), TRIAC (120V).
Minimum starting temp -4° F / -20°C

Lamping

Integrated LED modules capable of producing:
12W = 600 delivered lumens
20W = 1000 delivered lumens
Selectable 2700K, 3000K, 3500K, 4000K, 5000K (CCT).
Rated for 50,000 Hrs., 90 CRI.


Certification

All fixtures are cETLus listed for wet locations.
ADA
Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions
subject to change without notice.



Ordering Information:

White	Black	LED	Delivered Lumens	Adjustable CCT	H	W	D
WTNW0506LAJUDWH	WTNW0506LAJUDBK	12W	600	2700K/3000K/3500K/4000K/5000K	6"	5"	3-1/2"
WTNW0810LAJUDWH	WTNW0810LAJUDBK	20W	1000	2700K/3000K/3500K/4000K/5000K	9-1/2"	8"	3-1/2"