

ZSC15-INW

Wireless Occupancy Sensor, PIR, Ceiling Mount, 1500SF, White, Wireless Lighting Control

Requires DLDNK LuminaRF Stand Alone Room Controller or LU741 Lumina Gateway to operate. Wireless Sensor, Low Profile, Surface Mount, 1500 sq ft Field of View, 15 Second Transmitter, Color: White



Color :  White

UPC Code : 078477725450

Country Of Origin : Mexico

Technical Information

Electrical Specifications

Frequency : 2.4 Ghz

Environmental Specifications

Relative Humidity : 0% to 95% non-condensing

Storage Temperature Range : -4° to 158°F (-20° to 70°C)

Mechanical Specifications

Mounting Type : Ceiling Mount

Size : Width 4.20" (106.68mm), 1.57" Depth (39.87mm)

Performance Specifications

Coverage (Sq.Ft.) : 1500.0

Frequency Range : 75 FT

Pattern : 360°

Product Features

Battery : 7-10 years

Color : White

Feature : Wireless

Grade : Commercial

Mounting : Ceiling Mount

Mounting Height (Ft.) : 8-12 FT

Product Line : Wireless

Sensor Technology : Passive Infrared (PIR)

Sensor Type : Occupancy

Standards and Certifications

Listings : FCC ID: W7Z-ZICM357SP0, IC: 854A-ZICM357SP0, IC Certified (Canada) Listed. Can be used as a component in a system to meet energy code requirements for IECC, ASHRAE 90.1, and Title 24

Type

Product Type : Wireless Occupancy Sensor

Warranty

Warranty : 5-Year Limited

Features and Benefits

- Zero external power required
- Self-healing wire mesh network has no hard wired backbone and connects all products in the Lumina RF Eco-System together
- Robust and reliable true wireless sensors communicate with all transceivers via radio frequency

- _ Battery-powered wireless technology eliminates the need to pull additional wire, making installation quick and easy and increasing labor savings with little to no impact to business during conversion
- Walk-test mode
- Easy mounting
- Advanced field-of-view
- Meets Title 24, ASHRAE 90.1 and 2012 IECC energy code requirements

SPECIFICATION SUBMITTAL

JOB NAME: <input style="width: 95%; height: 20px;" type="text"/>	CATALOG NUMBERS: <input style="width: 45%; height: 20px;" type="text"/> <input style="width: 45%; height: 20px;" type="text"/>	
JOB NUMBER: <input style="width: 95%; height: 20px;" type="text"/>	<input style="width: 45%; height: 20px;" type="text"/> <input style="width: 45%; height: 20px;" type="text"/>	

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·

FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)

5386- 1797 ·

Visit our Website at: www.leviton.com

© 2026 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/company/about-leviton/locations

© 2026 Leviton Manufacturing Co., Inc.